

ИБП Eaton PW9305-15I-N - Powerware 9305 (20-60 кВА) - Брошюра по ИБП

Постоянная ссылка на страницу: https://eaton-power.ru/catalog/powerware-9305-7-5-30-kva/pw9305-15i-n/

FAT-N Powerware

Powerware 9305 Uninterruptible Power System

Product Focus 20-60 kVA



Features

- High load protection with double conversion online technology
- The unique Advanced Battery Management[™], providing significant longer battery life time
- Hot Sync™ parallel UPS systems for scalable redundancy and 7/24h load protection
- Transformerless UPS design with both static switch and maintenance bypass switch
- · Standard battery start and frequency converter features
- Software suite included

Product Snapshot

Technology: Double conversion

online (Series 9)

Rating: 20-60 kVA Voltage: 3x230/400 VAC Backup time: Typical 7-18 min

extendable up to hours

Poweware 9305, a Series 9
UPS, is designed to protect
computers and other critical
equipment in today's
centralised server rooms
and industrial automation
applications. The Powerware
9305 features a very wide
input voltage window with full
load, providing the capability
to operate from the mains
when most UPSs would be
discharging their batteries.

The Powerware 9305 operates using the unique Advanced Battery Management™ (ABM) function. While traditional UPS charges batteries continuously, UPS with ABM™ charges batteries only when necessary, thus preventing battery

corrosion. This exceptional ABM function prolongs the service life of batteries by up to 50%.

Furthermore, with the Hot Sync™ parallel load sharing technology, the absolute reliability of the UPS system can be increased by nearly 100%. The Hot Sync™ is designed for parallel redundant N+1 systems to satisfy 7/24h applications. This unique feature has the added advantage of erasing the single point of failure logic within the traditional load sharing systems, this is due to the ability of Hot Sync™ to synchronise and support the critical load independently of other UPS modules.



Hot Sync™ provides scalable and redundant power protection

Technical Specifications

POWERWARE 9305

General		
Rating	20-60 kVA at computer load	
Efficiency	Up to 94% online	
A I'll I	< 55 dB(A) 20-30 kVA	
Audible noise	< 60 dB(A) 40-60 kVA	
Input		
Nominal voltage	230/400 V	
Frequency	45-65 Hz	
Power factor	0,96	
Output		
Selectable voltage	220/380 V; 230/400 V; 240/415 V	
Regulation	±1% static	
Frequency	50 or 60 Hz	
Overload	Inverter 150% for 30 sec; 170% for 5 sec	

Battery				
Туре	Maintenance free VRLA batteries			
Battery charging	Advanced Battery Management (ABM™)			
Battery voltage	384 V (32 blocks) or 576 V (48 blocks)			
Options				
	Long life 10y battery cabinets			
	Input filter cabinets			
	Isolation transformer cabinets			
	Hot Sync™ parallel systems			
	ConnectUPS SNMP adapter			
	ViewUPS remote LCD panel			
Marking				
	CE, GOST			

Three phase input and output / basic models

9305 rating	Order code	Back-up	Dimensions (WxDxH)	Weight
20 kVA	1013992	7 min	520x788x1530 mm	400 kg
30 kVA	1020903	10 min	520x788x1530 mm	490 kg
40 kVA	1018617	— 10 min with ext. BATI-D W -	520x788x1530 mm	230 kg
BATI-D WIDE	1015467		520x788x1530 mm	550 kg
50 kVA	1014978	— 7 min with ext. BATI-D W -	520x788x1530 mm	260 kg
BATI-D WIDE	1015467		520x788x1530 mm	550 kg
60 kVA	1014514	— 10 min with ext. BATI-E -	520x788x1530 mm	260 kg
BATI-E	1011483		520x788x1530 mm	815 kg

In the interests of continual product improvement all specifications are subject to change without notice.

Powerware®, Hot Sync®, Advanced Battery Management, LanSafe, PowerVision, and FORESEER are trademark(s) of Eaton Power Quality Corporation. © 2005 Eaton Corporation

Mailing address: Powerware Products and Services, Marketing P.o. Box 54, 02921 Espoo, FINLAND Tel: +358 9 452 661 Fax: +358 9 452 66396

emea@powerware.com http://www.powerware.com

FATON

DENMARK Tel: +45 3686 7910 denmark.sales@powerware.com

FINLAND Tel: +358 9 452 661 finland.sales@powerware.com FRANCE Tel: +33 1 60 12 74 00 powerware.france@powerware.com

GERMANY Tel: +49 7841 6040 info.germany@powerware.com

ITALY Tel: +39 02 66 04 05 40 info@powerware.it

NORWAY Tel: +47 23 03 65 50

Tel: +48 22 331 85 24 poland.sales@powerware.com

RUSSIA Tel: +7 095 787 2890 russia.sales@powerware.com

SWEDEN

Tel: +46 8 598 940 00

> UNITED KINGDOM Tel: +44 1753-608 700 powerware.help@powerware.com

